

FEEDER RW90 – ALUMINUM

3 CONDUCTOR SIZE #2,#4 AWG XLPE,
600 V CSA, (-40°C)



Conductor:
2 AWG. (8000 series aluminum) compact class "B"
strand

Insulation:
Cross-linked Polyethylene (XLPE) Type RW90

Colour Coding:
Black, White, Red
Other colours available upon request

Print:
NORTHERN CABLES™ SIZE AWG or mm² COMPCT AL
ACM RW90 XLPE (-40C) 600V CSA, METER MARK

Applications:
For exposed wiring in dry, damp, or wet locations
For use in raceways, except cable trays, in dry, damp or wet locations.
For use in vaults and switch rooms as per the C.E.C part 1 table 19 and
rule 2202-2

Features:
Rated at 90°C wet, dry
Meets cold bend and impact tests at (-40°C)

Compliances:
Industry compliances: CSA Standard C22.2 No.38
RoHS

COND. SIZE (AWG/ kcmil)	NO OF COND	GROUND SIZE	MIN. AVG. INSULATION THICKNESS		NOMINAL DIAMETER (OVER)				NET WEIGHT
					INSULATION		CABLE		
			INCHES	mm	INCHES	mm	INCHES	mm	KG/KM
4	3	6	0.045	1.14	0.307	7.8	0.720	18.3	300
2	3	6	0.060	1.52	0.361	9.2	0.865	22.0	412

DIMENSIONS AND WEIGHTS ARE NOMINAL; SUBJECT TO INDUSTRY TOLERANCES